
 HATCHING INDICATES AREA TO BE KEPT CLEAR  
 INDICATES RECOMMENDED ERGONOMIC HEIGHT.

01	06/28/04	UPDATED TO CURRENT STANDARDS.	M.M.
REV	DATE	DESCRIPTION	DRFTR
<b>CONFIDENTIALITY</b> THIS DRAWING & THE INFORMATION CONTAINED THEREIN IS CONFIDENTIAL & PROPRIETARY TO INTEGRATED CIRCUIT DEVELOPMENT CORPORATION & MAY NOT BE TRACED, PHOTOGRAPHED, REPRODUCED IN ANY MANNER, NOR USED FOR ANY PURPOSE WHATSOEVER WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF INTEGRATED CIRCUIT DEVELOPMENT CORPORATION.		<b>UNLESS OTHERWISE NOTED</b> DIMENSIONS & TOLERANCING ARE IN INCHES (Millimeters) & PER ANSI-Y14.5 & ICD/HEATEFLEX DRAFTING STANDARDS. DECIMALS:   in       mm .XX           ±0.01     ±0.25 .XXX         ±0.005    ±0.127 .XXXX       ±0.0005   ±0.0127 X/XX         ±1/32      ±0.5* *             ±0.5*      ±0.5*	
DRAWN BY: M. Martinez   DATE: 06/20/03 DRAFTING OC: M.L.L.       DATE: 08-02-04		ENG/DSGN: J.T.       DATE: 08-02-04 APPROVED BY: J.T.   DATE: 8-2-04	
DWG. NO.: SSDI48-3N SHEET: 1 OF 6		TITLE: FACILITY & CLEARANCE REQUIREMENTS POSEIDON HP HEATING SYSTEM 48KW/208VAC/3-PH/60Hz SCALE: NONE FILE: F483N-R01	
		REV. 00	