

Configuration

Required Options (Default Model)
Additional Options (Blank if not needed)
PA060 - AFM1S - F12F16T - SFP1LC3

0 1 2 3 4 5 6 7 8 9

Default options highlighted


| 0. Model Size | |
|------------------|-----|
| Flow ≤ 60 L/min | 060 |
| Flow ≤ 140 L/min | 140 |

| 1. Shaft Seal | |
|---------------|---|
| Standard | A |
| Dry-Run | D |

| 2. Check Balls | |
|-----------------|---|
| PFA check balls | F |

| 3. Shift Mechanism | |
|--------------------|----|
| Magnetic shuttle | M1 |
| Timer mode | T1 |

| 4. Exhaust | |
|---------------------------------|---|
| <i>See #3 for compatibility</i> | |
| M1 Compatible | |
| Shuttle ports | S |
| Shuttle remote | R |
| T1 Compatible | |
| QEV | Q |
| QEV with Remote Exhaust | P |

| 5. In/Out Fitting(s) | | Compatible Model Size | |
|---|----------|-----------------------|-----|
| 6. Different 2nd Fitting | | | |
| <i>Only add 6 if different</i> | | | |
| Plugged fitting(s) | | B00 | B00 |
|  Flaretek Compatible | 1/2 in | F08 | F08 |
| | 3/4 in | F12 | F12 |
| | 1 in | F16 | F16 |
| | 1-1/4 in | F20 | F20 |
|  Pillar S-300 | 3/8 in | P06 | - |
| | 1/2 in | P08 | P08 |
| | 3/4 in | P12 | P12 |
| | 1 in | P16 | P16 |
| | 1-1/4 in | P20 | P20 |
|  FNPT | 1/2 in | N08 | - |
| | 3/4 in | N12 | N12 |
| | 1 in | N16 | N16 |
| | 1-1/4 in | - | N20 |
|  Primelock | 1/2 in | L08 | - |
| | 3/4 in | L12 | L12 |
| | 1 in | L16 | L16 |
| | 1-1/4 in | - | L20 |
|  Tube Adapter | 1/2 in | T08 | - |
| | 3/4 in | T12 | T12 |
| | 1 in | T16 | T16 |
| | 1-1/4 in | T20 | T20 |
| | 1-1/2 in | - | T24 |
|  Weldable | 3/4 in | W12 | W12 |
| | 1 in | W16 | W16 |

| 7. Fitting(s) Modifier | Out Port | |
|-------------------------|----------|-------|
| <i>Shipped detached</i> | | |
| Straight (2 qty) | Front | blank |
| Straight (2 qty) | Top | T |

| 8. Stroke Detection | | Model Size Compatibility | |
|--|-----------------------------|--------------------------|------|
| <i>See option #3 for compatibility</i> | | 60 | 140 |
| No stroke detection | | blank | |
| Pressure Switch | PNP/NPN, Single Sensor, 1 m | SFP1 | SGP1 |
| | PNP/NPN, Dual Sensor, 1 m | SFQ1 | SGQ1 |
| Fiber-Optics | D10 amplifier, 5 m | SFF5 | SGF5 |
| | D10 amplifier, 8 m | SFF8 | SGF8 |
| | No amplifier, 5 m | SFG5 | SGG5 |
| | No amplifier, 8 m | SFG8 | SGG8 |

| 9. Leak Detection | | |
|---------------------------------------|--------------------|-------|
| <i>See option 3 for compatibility</i> | | |
| No leak detection | | blank |
| Conductivity Leak Detect, 5 m | | LC5 |
| Conductivity Leak Detect, 8 m | | LC8 |
| Fiber-Optic | D10 Amplifier, 5 m | LF5 |
| | D10 Amplifier, 8 m | LF8 |
| | No Amplifier, 5 m | LG5 |
| | No Amplifier, 8 m | LG8 |

Contact support for revision or copy exact information.