

## Configuration

Required Options (Default Model)			Additional Options (Blank if not needed)			
<b>PSH015</b>	<b>-F08</b>	<b>-LF0</b>	<b>-SF0</b>	<b>-TF08</b>		
Pump Model	Check Balls	Inlet Fitting	Leak Detect	Stroke Detect	Outlet Fitting	Revision



## Instructions








Select all Required Options.  
 Only add Additional Options if desired.  
 Only add Outlet Fitting if different than Inlet Fitting.  
 Contact support for revision or copy exact information.

### Required Options

Default options are highlighted

Model	
Standard Model	PSH015
Dry-Run Capable	PSHSD015

Check Balls	
PTFE Check balls	blank
PFA Check balls	F

Inlet Fitting <i>Front straight only</i>		
	1/4 in.	F04
	3/8 in.	F06
	1/2 in.	F08
	3/4 in.	F12
	3/8 in.	T06
	1/2 in.	T08
	3/4 in.	T12
	1/2 in.	W08
	3/4 in.	W12
	1/8 in.	P02
	1/4 in.	P04
	3/8 in.	P06
	1/2 in.	P08
	3/4 in.	P12
	1/4 in.	N04
	3/8 in.	N06
	1/2 in.	N08
	3/4 in.	N12
	3/8 in.	S06
	1/2 in.	S08
	3/4 in.	S12
	1/2 in.	L08
	3/4 in.	L12

### Additional Options











Leak Detection	
No leak detection	blank
15 ft fiber optic cable with no amplifier	LF0
15 ft fiber optic cable with D10 amplifier	LF1
25 ft fiber optic cable with no amplifier	LF2
25 ft fiber optic cable with D10 amplifier	LF3
15 ft conductivity cable	LC0
25 ft conductivity cable	LC1

Stroke Detection	
No stroke detection	blank
15 ft fiber optic cable with no amplifier	SF0
15 ft fiber optic cable with D10 amplifier	SF1
25 ft fiber optic cable with no amplifier	SF2
25 ft fiber optic cable with D10 amplifier	SF3
Single NPN Pressure Switch	SP1
Dual NPN Pressure Switches * <i>(Includes two DP2 pressure switches)</i>	SP2
Dual Pressure Switch * <i>(No pressure switches included)</i> <i>Sensors are required for operation.</i>	SP3
Single PNP Pressure Switch	SP4
Dual PNP Pressure Switches * <i>(Includes two DP2 pressure switches)</i>	SP5

\* White Knight shuttle valve not included.



Timer mode operation requires end-of-stroke detection. Use of timer mode without stroke detection voids the warranty.

Outlet Fitting <i>Straight only.</i> <i>Select Top or Front.</i>		Front	Top	
Same as Inlet Fitting		blank	n/a	
	1/4 in.	FF04	TF04	
	3/8 in.	FF06	TF06	
	1/2 in.	FF08	TF08	
	3/4 in.	FF12	TF12	
	3/8 in.	FT06	TT06	
	1/2 in.	FT08	TT08	
	3/4 in.	FT12	TT12	
	1/2 in.	FW08	TW08	
	3/4 in.	FW12	TW12	
		1/8 in.	FP02	TP02
		1/4 in.	FP04	TP04
3/8 in.		FP06	TP06	
1/2 in.		FP08	TP08	
	3/4 in.	FP12	TP12	
		1/4 in.	FN04	TN04
		3/8 in.	FN06	TN06
1/2 in.		FN08	TN08	
	3/4 in.	FN12	TN12	
		3/8 in.	FS06	TS06
		1/2 in.	FS08	TS08
	3/4 in.	FS12	TS12	
		1/2 in.	FL08	TL08
3/4 in.		FL12	TL12	

Leave blank if Front and same as Inlet Fitting.  
 Select option if Top or different than Inlet Fitting.

Revision	
No revision	blank
<p>Contact White Knight support for revision level or copy exact code activation details. Configured part numbers are not Copy Exact Part Numbers.                      Email: <a href="mailto:support@wkfluidhandling.com">support@wkfluidhandling.com</a>                      Phone: 435.783.6040</p>	